



Drying cabinet



MICROPROCESSOR CONTROLLED

Microprocessor controlled evacuating drying cabinet. Illuminated and with two automatic and three manually, time controlled programs. The automatic programs are turned off when the laundry is dry.

TS 6 MP is delivered in one piece, ready to use. TS 9 MP is delivered as flat pack for delivery reasons and must be assembled before use.

Choose between automatic or normal drying programs.



Standard equipment

- Microprocessor controlled evacuating drying cabinet with double doors.
- Effective lights.
- TS 6 MP in grey "Skinplate"
- TS 9 MP in gray aluzink steel plate.
- Stable swinging, hanging rails.
- The program panel is placed on the left side, at comfortable working height (TS 6 MP).
- Recirculation system, hot air.
- Adjustable feet, 4 pcs.

Microprocessor

- Two automatic drying programs; "cupboard dry" and "ironing dry."
- Three manually time controlled drying programs; 30°, 50° and 70 °C.
- The automatic programs ends when set residual moisture is reached.
- Possible to upgrade.
- Automatic "cool-down" the last 10 minutes of the drying process.

Optional extras

- Drying frame to be placed on the door with hooks for small garments like gloves, socks etc. Part No 131011.
- Single bar.

Illuminated drying cabinet.



Main specifications

	TS 6 MP	TS 9 MP
Loading capacity, kg/lbs	6-8/13,22-17,63	8-10/17,63-22,04
Drying capacity, g/min *	67	67
Heating effect, KW	6,0	9,0
Total effect, KW	6,3	9,3
Consumption data		
Drying time, max, min	90	90
Energy consumption/kg, kWh	0,8	0,8
Part No	131020	131022

* Valid for 6 kgs of cotton with a moisture retention of 55%.

GOUD Laundry Solutions

gouda b.v. | 3284TJ - IJsselmeerdijk - Ltd. | 0186-370096 - Fax: 0123-379647
www.gooud.nl | info@gooud.nl

TS 6 MP - TS 9 MP



Technical specification



TS 6 MP - TS 9 MP

	TS 6 MP	TS 9 MP
Electrical connections		
Electrical connection*	3-N, 400 V, 50 Hz	
Fuse, A	10	16
Total effect, kW	6,3	9,3
Heating elements, kW	6,0	9,0
Air connections		
Outlet exhaust, ø mm/Inch	125/4,92	125/4,92
Outlet air flow, m ³ /h	170	170
Pressure drop, max Pa	80	80
Sound level		
Airborne sound level, dB(A)	50	50
Shipping data		
Net, kg/lbs	145/319,67	165/363,76
Crated, kg/lbs	20/44,09	35/77,16
Shipping data net, kg/lbs	165/363,76	200/440,92
Shipping volume, m ³	1,85	1,90
Optional extras		
Air exchanger 1 vert., 125 mm/4,92 inch	141009	141009
Air exchanger 2 vert., 160 mm/6,3 inch	141018	141018
Dimensions		
Width, mm/Inch	1200/47,24	1700/66,92
Depth, mm/Inch	690/26,77	750/29,52
Height, mm/Inch	1930/75,98	2090/81,89

* Other voltage on request.



paukenslag 1 - 3286TD - Klaaswaal = tel: 0186-576050 - Fax: 0186-575047
www.laundrysolutions.nl - info@laundrysolutions.nl